













### 1.3 Package Listing

Product/Pic	QTY	Product/Pic	QTY	Product/Pic	QTY
	1 set	 Instruction Sheet	1 copy	 Push-fit connector	1 set
 1/2" to 1/4" Push-fit connector PE shut off valve	1 pc	 1/2" to 1/4" Push-fit connector	1 pc	 1/2" to 3/8" Push-fit connector	1 pc
 1/4" & 3/8" pipe	2.5M of each	 Hose nail for 1/4" & 3/8" pipe	5pcs of each	 5X80 expansion screws	2 pcs
(Optional accessories)					
 filter	1 pc	 1/4" Push-fit connector	2 pcs	 Mounting clip / 5X30 expansion screw	2pcs of each

## 2 Product Parameter

### 2.1 Parameters

Input Voltage	100~240ACV 50/60Hz	N.W	4.5 kg	Ambient Temperature	≤50℃
Power	120 W	G.W	6.5kg	Ambient Humidity	≤80%RH
Mist Output	1.6 KG/Hr	Dimension	362X206X550 mm	Atomizing Media	(demineralized) Tap-water
Mist Particle Dia (D90)	≤10μm	Max Atomizing Distance	3.5m	Water Temperature	10~55℃
Mist Particle Dia (D50)	≤5μm	Noise	≤55dB	Water Pressure	0.1~0.5MPa

### 2.2 Operating Principles




Chart 2.1