

TABELLA SCELTA UGELLO TESTINA - NOZZLE SELECTION CHART FOR CLEANING HEADS

Fatt.Portata		M4 (CORTI) (0°)	M4 (0°)	1/4 NPT (5°) Standard	Con ventolina With flow straightener		
SIZE	↓				1/8 NPT (0°) Standard	1/4 NPT (0°) Standard	1/4 NPT (0°) Prol-Extended
O2	4,6 1,2	80.0350.51	25.1190.51		16.1363.20		
O23	5,0 1,3		25.1191.51				
O25	5,6 1,5	80.0351.51	25.1091.51				
O27	6,1 1,6		25.1192.51				
O3	6,7 1,8	80.0352.51	25.1092.51	16.1305.30	16.1363.30	16.1380.30	
O32	7,1 1,9		25.1193.51				
O35	7,8 2,1	80.0353.51	25.1093.51			16.1380.35	
O37	8,4 2,2		25.1098.51				
O4	9,1 2,4	80.0354.51	25.1094.51	16.1305.40	16.1363.40	16.1380.40	
O43	9,7 2,6		25.1194.51				
O45	10,3 2,7		25.1095.51		16.1363.45	16.1380.45	
O5	11,2 3,0		25.1195.51	16.1305.50	16.1363.50	16.1380.50	
O53	12,0 3,2		25.1196.51				
O55	12,6 3,3		25.1197.51			16.1380.55	
O6	13,7 3,6		25.1186.51	16.1305.60	16.1363.60	16.1380.60	
O65	14,8 3,9		25.1198.51			16.1380.65	
O7	16,0 4,2		25.1199.51	16.1305.70	16.1363.70	16.1380.70	80.0418.23
O8	18,2 4,8		25.1085.51	16.1305.80	16.1363.80		80.0419.23
O9	21,0 5,5				16.1363.90		80.0420.23
O95	22,0 5,8						80.0421.23
11	25,0 6,6						80.0422.23
12	27,0 7,1						80.0423.23
13	30,0 7,9						80.0424.23
14	32,0 8,5						80.0425.23
15	34,0 9,0				16.1363.15		80.0426.23
16	36,0 9,5						80.0427.23
18	41,0 10,8						80.0428.23
19	43,0 11,4						80.0429.23
20	46,0 12,2						80.0430.23
25	57,0 15,1						80.0435.23
30	68,0 18,0						80.0440.23